




ENERG

енергия · ενεργεια



OCHSNER

AQUA 17 HSTA



55 °C

35 °C

A+++

A+++

A+++

A++

A+

A

B

C

D



47 dB



■ 14 kW

■ 17 kW

■ 14 kW

■ 17 kW

■ 14 kW

■ 17 kW



2019

811/2013

Heatpump datasheet:

Manufacturer:	OCHSNER
Model:	AQUA 17 HSTA

Information concerning energy efficiency class and rated heat output:

	average/low	average/medium
Energy efficiency class space heater:	A+++	A+++
Rated heat output:	17 kW	14 kW
Energy efficiency space heater:	250.0 %	159.0 %
Annual final energy consumption space heater:	5263 kWh	6965 kWh
Sound power level indoors	47 dB(A)	

Special precautions concerning assembly, installation or maintenance:

The system was sized, connected, laid out and filled in accordance with applicable standards, regulations and ordinances by a qualified contractor. If the system consists of several sections, these must be connected and installed using original OCHSNER accessories as supplied by OCHSNER. System sections must be connected via the shortest route possible and must not exceed a connection distance of 5 m. In accordance with the operating and installation manual, the system is used as intended for a private building heating system. Commissioning must only be carried out by OCHSNER Customer Service. Maintenance and inspection according to the manufacturer's instructions must be carried out at least every 12 months unless legal requirements and ordinances specify a shorter interval.

Additional information:	low	medium
Rated heat output colder climate:	17 kW	14 kW
Rated heat output warmer climate:	17 kW	14 kW
Energy efficiency space heater colder climate:	260.0 %	164.0 %
Energy efficiency space heater warmer climate:	250.0 %	158.0 %
Annual energy consumption space heater colder climate:	6045 kWh	8055 kWh
Annual energy consumption space heater warmer climate:	3399 kWh	4513 kWh

Technical data of the temperature controller:

Manufacturer:	OCHSNER	
Model:	OTE controller	
Controller class with room remote control:	VII	-
Contribution of the controller to the energy efficiency space heater with room remote control:	3.5	%
Controller class without room remote control:	III	-
Contribution of the controller to the energy efficiency space heater without room remote control:	1.5	%

Model:	AQUA 17 HSTA
	Water heating heat pump
Low-temperature heat pump:	no
Equipped with a supplementary heater:	no
Heat pump combination heater:	no
Temperature application:	low
Climate conditions:	colder

Item	Symbol	Value
Rated heat output (*)	Prated	17 kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	Pdh	16.9 kW
$T_j = +2\text{ °C}$	Pdh	17.1 kW
$T_j = +7\text{ °C}$	Pdh	17.3 kW
$T_j = +12\text{ °C}$	Pdh	17.3 kW
$T_j =$ bivalent temperature	Pdh	16.6 kW
$T_j =$ operation limit temperature	Pdh	16.6 kW
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	Pdh	16.8 kW
Bivalent temperature	T_{biv}	-22 °C
Power input „compressor off“		0 W
Power consumption in modes other than active mode		
Off mode	P_{OFF}	20 W
Thermostat-off mode	P_{TO}	20 W
Standby mode	P_{SB}	20 W
Crankcase heater mode	P_{CK}	0 W
Other items		
Capacity control		fixed
Sound power level	indoors	L_{WA} 47 dB
	outdoors	
Annual energy consumption	Q_{HE}	6045 kWh
For heat pump combination heater:		
Declared load profile		-
Daily electricity consumption	Q_{elec}	-

Item	Symbol	Value
Seasonal space heating energy efficiency	η_s	260.0 %
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	COPd	6.56
$T_j = +2\text{ °C}$	COPd	7.00
$T_j = +7\text{ °C}$	COPd	7.35
$T_j = +12\text{ °C}$	COPd	7.45
$T_j =$ bivalent temperature	COPd	5.93
$T_j =$ operation limit temperature	COPd	5.93
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COPd	6.35
For air-to-water heat pumps: Operation limit temperature	TOL	-22 °C
Heating water operating limit temperature	WTOL	68 °C
Supplementary heater		
Rated heat output (*)	P_{sup}	0.00 kW
Type of energy input		electricity
For air-to-water heat pumps: Rated air flow rate, outdoors	-	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3000 l/h
Water heating energy efficiency	η_{wh}	-
Daily fuel consumption	Q_{fuel}	-

Contact details OCHSNER Wärmepumpen GmbH, Ochsner-Straße 1, A-3350 Haag

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating-Pde-signh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(T_j).

Model:	AQUA 17 HSTA
	Water heating heat pump
Low-temperature heat pump:	no
Equipped with a supplementary heater:	no
Heat pump combination heater:	no
Temperature application:	medium
Climate conditions:	colder

Item	Symbol	Value
Rated heat output (*)	Prated	14 kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	Pdh	15.1 kW
$T_j = +2\text{ °C}$	Pdh	15.7 kW
$T_j = +7\text{ °C}$	Pdh	16.1 kW
$T_j = +12\text{ °C}$	Pdh	16.4 kW
$T_j =$ bivalent temperature	Pdh	14.3 kW
$T_j =$ operation limit temperature	Pdh	14.3 kW
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	Pdh	14.8 kW
Bivalent temperature	T_{biv}	-22 °C
Power input „compressor off“		0 W
Power consumption in modes other than active mode		
Off mode	P_{OFF}	20 W
Thermostat-off mode	P_{TO}	20 W
Standby mode	P_{SB}	20 W
Crankcase heater mode	P_{CK}	0 W
Other items		
Capacity control		fixed
Sound power level	indoors	L_{WA} 47 dB
	outdoors	
Annual energy consumption	Q_{HE}	8055 kWh
For heat pump combination heater:		
Declared load profile		-
Daily electricity consumption	Q_{elec}	-

Item	Symbol	Value
Seasonal space heating energy efficiency	η_s	164.0 %
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	COPd	4.04
$T_j = +2\text{ °C}$	COPd	4.63
$T_j = +7\text{ °C}$	COPd	5.19
$T_j = +12\text{ °C}$	COPd	5.67
$T_j =$ bivalent temperature	COPd	3.33
$T_j =$ operation limit temperature	COPd	3.33
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COPd	3.71
For air-to-water heat pumps: Operation limit temperature	TOL	-22 °C
Heating water operating limit temperature	WTOL	68 °C
Supplementary heater		
Rated heat output (*)	P_{sup}	0.00 kW
Type of energy input		electricity
For air-to-water heat pumps:		
Rated air flow rate, outdoors	-	-
For water-/brine-to-water heat pumps:		
Rated brine or water flow rate, outdoor heat exchanger	-	3000 l/h
Water heating energy efficiency		
	η_{wh}	-
Daily fuel consumption		
	Q_{fuel}	-

Contact details OCHSNER Wärmepumpen GmbH, Ochsner-Straße 1, A-3350 Haag

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating-Pde-signh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(T_j).

Model:	AQUA 17 HSTA
	Water heating heat pump
Low-temperature heat pump:	no
Equipped with a supplementary heater:	no
Heat pump combination heater:	no
Temperature application:	low
Climate conditions:	average

Item	Symbol	Value
Rated heat output (*)	Prated	17 kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	Pdh	16.6 kW
$T_j = +2\text{ °C}$	Pdh	16.9 kW
$T_j = +7\text{ °C}$	Pdh	17.1 kW
$T_j = +12\text{ °C}$	Pdh	17.4 kW
$T_j =$ bivalent temperature	Pdh	16.6 kW
$T_j =$ operation limit temperature	Pdh	16.6 kW
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	Pdh	16.6 kW
Bivalent temperature	T_{biv}	-10 °C
Power input „compressor off“		0 W
Power consumption in modes other than active mode		
Off mode	P_{OFF}	20 W
Thermostat-off mode	P_{TO}	20 W
Standby mode	P_{SB}	20 W
Crankcase heater mode	P_{CK}	0 W
Other items		
Capacity control		fixed
Sound power level	indoors	L_{WA} 47 dB
	outdoors	
Annual energy consumption	Q_{HE}	5263 kWh
For heat pump combination heater:		
Declared load profile		-
Daily electricity consumption	Q_{elec}	-

Item	Symbol	Value
Seasonal space heating energy efficiency	η_s	250.0 %
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	COPd	6.01
$T_j = +2\text{ °C}$	COPd	6.49
$T_j = +7\text{ °C}$	COPd	6.97
$T_j = +12\text{ °C}$	COPd	7.51
$T_j =$ bivalent temperature	COPd	5.93
$T_j =$ operation limit temperature	COPd	5.93
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COPd	5.93
For air-to-water heat pumps: Operation limit temperature	TOL	-10 °C
Heating water operating limit temperature	WTOL	68 °C
Supplementary heater		
Rated heat output (*)	P_{sup}	0.00 kW
Type of energy input		electricity
For air-to-water heat pumps: Rated air flow rate, outdoors	-	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3000 l/h
Water heating energy efficiency	η_{wh}	-
Daily fuel consumption	Q_{fuel}	-

Contact details OCHSNER Wärmepumpen GmbH, Ochsner-Straße 1, A-3350 Haag

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating-Pde-signh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(T_j).

Model:	AQUA 17 HSTA
	Water heating heat pump
Low-temperature heat pump:	no
Equipped with a supplementary heater:	no
Heat pump combination heater:	no
Temperature application:	medium
Climate conditions:	average

Item	Symbol	Value
Rated heat output (*)	Prated	14 kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j		
T _j = -7 °C	Pdh	14.5 kW
T _j = +2 °C	Pdh	15.3 kW
T _j = +7 °C	Pdh	15.8 kW
T _j = +12 °C	Pdh	16.3 kW
T _j = bivalent temperature	Pdh	14.3 kW
T _j = operation limit temperature	Pdh	14.3 kW
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	Pdh	14.3 kW
Bivalent temperature	T _{biv}	-10 °C
Power input „compressor off“		0 W
Power consumption in modes other than active mode		
Off mode	P _{OFF}	20 W
Thermostat-off mode	P _{TO}	20 W
Standby mode	P _{SB}	20 W
Crankcase heater mode	P _{CK}	0 W
Sonstige Elemente		
Capacity control	fixed	
Sound power level	indoors	L _{WA} 47 dB
	outdoors	-
Annual energy consumption	Q _{HE}	6965 kWh
For heat pump combination heater:		
Declared load profile	-	
Daily electricity consumption	Q _{elec}	-

Item	Symbol	Value
Seasonal space heating energy efficiency	η _s	159.0 %
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j		
T _j = -7 °C	COPd	3.50
T _j = +2 °C	COPd	4.20
T _j = +7 °C	COPd	4.74
T _j = +12 °C	COPd	5.40
T _j = bivalent temperature	COPd	3.33
T _j = operation limit temperature	COPd	3.33
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	COPd	3.33
For air-to-water heat pumps: Operation limit temperature	TOL	-10 °C
Heating water operating limit temperature	WTOL	68 °C
Supplementary heater		
Rated heat output (*)	P _{sup}	0.00 kW
Type of energy input	electricity	
For air-to-water heat pumps:		
Rated air flow rate, outdoors	-	-
For water-/brine-to-water heat pumps:		
Rated brine or water flow rate, outdoor heat exchanger	-	3000 l/h
Water heating energy efficiency		
	η _{wh}	-
Daily fuel consumption		
	Q _{fuel}	-

Contact details OCHSNER Wärmepumpen GmbH, Ochsner-Straße 1, A-3350 Haag

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating-Pde-signh, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j).

Model:	AQUA 17 HSTA
	Water heating heat pump
Low-temperature heat pump:	no
Equipped with a supplementary heater:	no
Heat pump combination heater:	no
Temperature application:	low
Climate conditions:	warmer

Item	Symbol	Value
Rated heat output (*)	Prated	17 kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	Pdh	16.6 kW
$T_j = +2\text{ °C}$	Pdh	16.6 kW
$T_j = +7\text{ °C}$	Pdh	16.8 kW
$T_j = +12\text{ °C}$	Pdh	17.2 kW
$T_j =$ bivalent temperature	Pdh	16.6 kW
$T_j =$ operation limit temperature	Pdh	16.6 kW
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	Pdh	16.6 kW
Bivalent temperature	T_{biv}	2 °C
Power input „compressor off“		0 W
Power consumption in modes other than active mode		
Off mode	P_{OFF}	20 W
Thermostat-off mode	P_{TO}	20 W
Standby mode	P_{SB}	20 W
Crankcase heater mode	P_{CK}	0 W
Sonstige Elemente		
Capacity control		fixed
Sound power level	indoors	L_{WA} 47 dB
	outdoors	-
Annual energy consumption	Q_{HE}	3399 kWh
For heat pump combination heater:		
Declared load profile		-
Daily electricity consumption	Q_{elec}	-

Item	Symbol	Value
Seasonal space heating energy efficiency	η_s	250.0 %
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	COPd	5.93
$T_j = +2\text{ °C}$	COPd	5.93
$T_j = +7\text{ °C}$	COPd	6.38
$T_j = +12\text{ °C}$	COPd	7.51
$T_j =$ bivalent temperature	COPd	5.93
$T_j =$ operation limit temperature	COPd	5.93
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COPd	5.93
For air-to-water heat pumps: Operation limit temperature	TOL	2 °C
Heating water operating limit temperature	WTOL	68 °C
Supplementary heater		
Rated heat output (*)	P_{sup}	0.00 kW
Type of energy input		electricity
For air-to-water heat pumps: Rated air flow rate, outdoors	-	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3000 l/h
Water heating energy efficiency	η_{wh}	-
Daily fuel consumption	Q_{fuel}	-

Contact details OCHSNER Wärmepumpen GmbH, Ochsner-Straße 1, A-3350 Haag

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating-Pde-signh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(T_j).

Model:	AQUA 17 HSTA
	Water heating heat pump
Low-temperature heat pump:	no
Equipped with a supplementary heater:	no
Heat pump combination heater:	no
Temperature application:	medium
Climate conditions:	warmer

Item	Symbol	Value
Rated heat output (*)	Prated	14 kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	Pdh	14.3 kW
$T_j = +2\text{ °C}$	Pdh	14.3 kW
$T_j = +7\text{ °C}$	Pdh	15.0 kW
$T_j = +12\text{ °C}$	Pdh	16.0 kW
$T_j =$ bivalent temperature	Pdh	14.3 kW
$T_j =$ operation limit temperature	Pdh	14.3 kW
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	Pdh	14.3 kW
Bivalent temperature	T_{biv}	2 °C
Power input „compressor off“		0 W
Power consumption in modes other than active mode		
Off mode	P_{OFF}	20 W
Thermostat-off mode	P_{TO}	20 W
Standby mode	P_{SB}	20 W
Crankcase heater mode	P_{CK}	0 W
Other items		
Capacity control		fixed
Sound power level	indoors	L_{WA} 47 dB
	outdoors	
Annual energy consumption	Q_{HE}	4513 kWh
For heat pump combination heater:		
Declared load profile		-
Daily electricity consumption	Q_{elec}	-

Item	Symbol	Value
Seasonal space heating energy efficiency	η_s	158.0 %
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j		
$T_j = -7\text{ °C}$	COPd	3.33
$T_j = +2\text{ °C}$	COPd	3.33
$T_j = +7\text{ °C}$	COPd	3.87
$T_j = +12\text{ °C}$	COPd	4.95
$T_j =$ bivalent temperature	COPd	3.33
$T_j =$ operation limit temperature	COPd	3.33
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COPd	3.33
For air-to-water heat pumps: Operation limit temperature	TOL	2 °C
Heating water operating limit temperature	WTOL	68 °C
Supplementary heater		
Rated heat output (*)	P_{sup}	0.00 kW
Type of energy input		electricity
For air-to-water heat pumps: Rated air flow rate, outdoors	-	-
For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3000 l/h
Water heating energy efficiency	η_{wh}	-
Daily fuel consumption	Q_{fuel}	-

Contact details OCHSNER Wärmepumpen GmbH, Ochsner-Straße 1, A-3350 Haag

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating-Pde-signh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(T_j).